

The A-220 Small-Bore Self-Centering Target

The ideal alignment tool for tube-sheet bore straightness, large gun barrel straightness, and small extruder barrel alignment

Target Features

Hamar Laser's A-220 Small-Bore, Self-Centering Target is designed specifically to measure the straightness of small bores, from .70 in. (18 mm) to 1.5 in. (38 mm). This small, lightweight, compact target self-centers to an accuracy of .0005 in. (0.013 mm) and has a sensor area of 4 x 4 mm.

Target features include:

- 3 ft. (1 m) carbon fiber insertion pole with connector (can be folded to 1.5 ft.). Extra lengths of pole are available for bores up to 10 feet (3 m) long.
- The target is customized for each bore, but can accommodate diameter changes of $\pm .010$ in. (0.25 mm) without affecting the ability to self-center in the bore.
- 4 x 4 mm PSD (Position Sensing Detector) is concentric to bore ID to $> .0005$ in. (0.013 mm).
- .00002 in. (0.0005 mm) resolution when used with the R-1307 Readout.
- .654 in. (16.6 mm) OD, with tungsten carbide, precision-ground measuring balls (feet) and a tapered end for easy insertion in bores.
- Accommodates bores from .70 in. (18 mm) to 1.5 in. (38 mm).
- Can be used with the R-1307C or R-1307 2.4ZB target readouts. Use the A-910-2.4ZB Radio Receiver for a PC with the R-1307-2.4ZB for wireless data downloads to our Bore9 software.
- Spirit level orients the PSD sensor axes to the alignment axes of the bore.



The A-220 Small-Bore, Self-Centering Target



**HAMAR
LASER**®
ALIGN WITH THE BEST

5 Ye Olde Road, Danbury, CT 06810 USA

Phone: (800) 826-6185 or +1-203-730-4600 • Fax: +1-203-730-4611

E-mail: sales@hamarlaser.com • Internet: <http://www.hamarlaser.com>

For a list of our distributors, please visit: http://www.hamarlaser.com/intl_distributors.htm

Specifications

The A-220 Small-Bore Self-Centering Target

- Size:** .654 in. (16.6 mm) OD. 1.72 in. (43.7 mm) long without pole.
- Sensor Size/Resolution:** 4 x 4 mm PSD with .0001 in. (0.001 mm) resolution when used with the R-1307.
- Sensor Concentricity to Target Housing:** < .0005 in. (0.013 mm)
- Material:** 303 stainless steel
- Cable:** Hard-mounted 10 ft. (3m) cable mounted inside the inserted pole with Lemo connector.
- Weight:** 5 oz. (85 g).
- | | | | | | | |
|---|---|-----------|-------|---|----|---|
| m | Ø | 6,2eouVE6 | 6g3u6 | 6 | 36 | 3 |
|---|---|-----------|-------|---|----|---|
- Bore Diameter Range:** Can accommodate $\pm .010$ in. (0.25 mm) diameter change and still self-center. Requires 1 target for each bore ID.
- Insertion Pole:** 3 ft, (1 m) in two 1.5 ft. pieces. Extra lengths of pole are available up to 10 ft. (3 m).

